

SABA, a strong bond

### Description

SABA 914 is a brushable adhesive based on flammable solvents for the bonding of rigid PVC materials. SABA 914 is especially appropriate for the bonding of calibrated rigid PVC piping.

Solvent based adhesives

### Special properties

- Appropriate for the bonding of PVC, PVC-c and ABS-piping
- Good resistance to weak bases and acids

MSP sealants

### Method of use

Clean both parts with SABA PVC & ABS Cleaner. Apply adhesive equally with brush in the longitudinal direction. Please mate parts immediately and remove superfluous adhesive. Clean brush with SABA PVC & ABS Cleaner.

Water based adhesives

### Technical data

Silicone sealants

Viscosity at 23 °C	: approx. 55 mPa.s
Density	: approx. 890 kg/m <sup>3</sup>
Solids content	: approx. 15%
Open time	: approx. 24 hours
Coverage	: approx. 150 - approx. 200 gr./ m <sup>2</sup>
Clean with	: SABA PVC & ABS Cleaner
Hotmelts	Work temperature : minimum + 15 °C (R.H. not above 70%)
	Storage temperature : minimum + 5 °C and maximum +35 °C
	Temperature resistance : approx. 90 °C
Epoxy products	Shelf life : 18 months in unopened packing

Foam coatings

Hotmelts

Epoxy products

### Order information

PU products

Packing	100 ml tin with brush	250 ml tin with lid and brush	1 litre can	6 litres can	200 litres drum
Contents				5 kg	178 kg

Polysulfide products

Primers

Colour	white/ transparent
Article No.	100177

Cleaning agents

### Safety indications

See the corresponding material safety data sheet.



### SABA Dinxperlo BV

Industriestraat 3, NL-7091 DC Dinxperlo, PO Box 3, NL-7090 AA Dinxperlo, the Netherlands, Tel +31 (0) 315 658999, Fax +31 (0) 315 653207, E-mail info@saba.nl, Internet www.saba.nl.

*Our application instructions and technical advice are based on our actual level of knowledge. We cannot accept any liability for conclusions and recommendations resulting from these. Buyers and/or users should judge the suitability of our products for any envisaged application by preliminary testing. The general terms and conditions for the members of the "Nederlandse Vereniging van Rubber- en Kunststoffabrikanten (NVR)" apply on all our deliveries.*

Version number: 2004/07