

SABA, a strong bond

Description

SABA Seal One is a one component sealant. SABA Seal One is especially suitable for sealing teak ship decks

Solvent based adhesives

Special properties

- Excellent aging resistance
- No bubble formation during polymerisation

MSP sealants

Method of use

Treat the sides of the joints with SABA Primer S1
Apply separation tape to the bottom of the joints to prevent three-point adherence

Water based adhesives

Apply SABA Seal One with hand gun or air pressure gun
Detailed application instructions are given in system descriptions SBS -1 and SBS -5

Silicone sealants

Technical data

Foam coatings

Basis	: silane modified polymers
Consistence	: pasty
Density	: approx. 1340 kg/m ³
Solids content	: approx. 100%
Hotmelts	Skin time : approx. 10 minutes at 23 °C / 75% rh
	Tack-free after : approx. 4 hours
	Curing rate : approx. 3 mm/24 hrs at 23 °C / 75% rh
Epoxy products	Volume alteration (DIN 52451) : approx. -5%
	Hardness Shore A (DIN 53505): 20
PU products	Module at 100% : 0.75 N/mm ²
	Tensile strength : 1.45 N/mm ²
	Elongation at break : 400%
	Work temperature : minimum +5 °C
Polysulfide products	Storage temperature : minimum +5 °C
	Temperature resistance : approx. from -30 °C up to +80 °C
	Shelf life : 15 months in unopened packing

Primers

Order information

Cleaning agents

Packing	cartridge	aluminium foil bag
Content	290 ml	600 ml

Colour	black RAL 7021
Article No.	100205

Safety recommendations

See the corresponding material safety data sheet



SABA Dinxperlo BV

Industriestraat 3, NL-7091 DC Dinxperlo, PO Box 3, NL-7090 AA Dinxperlo, the Netherlands, Tel +31 (0) 315 658999, Fax +31 (0) 315 653207, E-mail info@saba.nl, Internet www.saba.nl.

Our application instructions and technical advice are based on our actual level of knowledge. We cannot accept any liability for conclusions and recommendations resulting from these. Buyers and/or users should judge the suitability of our products for any envisaged application by preliminary testing. The general terms and conditions for the members of the "Nederlandse Vereniging van Rubber- en Kunststoffabrikanten (NVR)" apply on all our deliveries.

Version number: 0703